



for Better Quality & Durability

CC - CURING COMPOUND

DESCRIPTION

CETEX-CC, Curing Compound, when applied to freshly placed concrete, quickly forms a moisture vapour resistant membrane to maximize water retention for better cement hydration and concrete strength.

ADVANTAGES

- ❶ Reduces Surface shrinkage & crack formation by eliminating moisture loss from surface.
- ❷ Reduces surface dusting as capillary migration of water to surface is eliminated.
- ❸ Reduces cost of labour and supervision cost compared to conventional ponding.
- ❹ Eliminates the need of damp Hessian, sand or plastic for curing or surface protection.
- ❺ Rapid film formation; enables concrete to hydrate more efficiently.
- ❻ Non flammable, Non toxic, very low VOC, conforms to green building norms.
- ❼ It is economical to use and for large areas may work out cost effective.

PROPERTIES

Type	:	Wax emulsion in water
Color	:	White liquid
Specific Gravity	:	1.0 +/- 0.02 at 25°C
pH	:	7.0 – 8.0
Solid content	:	31% +/- 1.0

COVERAGE

1 kg will cover approx 5.0 sq. mtr. Do not spread too thin

DIRECTION OF USE

CETEX-CC should be mixed thoroughly before application. It can be applied by spray or by brush. The compound should be applied as soon as possible after the concrete is free of surface water. For large area spray application is preferred. Nozzle of spray should be at approx. 450mm above the surface. **Do not dilute.**

PACKING

CETEX-CC is available in 20kg or 50 kg pack.

STORAGE

CETEX-CC has self life of 18 months. Store it in frost-free condition away from sunlight or extreme heat. For best result, keep the container airtight to prevent surface evaporation.